






LOAD SLIDE

INSTALLATION INSTRUCTIONS

**A**


1X

B

1X

C


4X

D

4X

E


4X

F


2X

G


4X

H

4X

I

4X

J


4X

K


16X

L

16X

M


16X

N


20X



1




Ensure there is a clearance gap of between 5-10mm from the handle to the tailgate.



2


Centre the frame in the middle of the tub allowing even gaps between wheel arches.




3

Mark and pick relevant drill holes.

4



CAUTION: Before drilling, check to ensure no important or hazardous items are positioned beneath the drill points such as spare tyre, fuel lines/ tank or wiring.




5

Ensure the spacers are placed underneath the frame. Pick relevant spacer according to fitting.



Item I, M10 nylock nut, to be installed last. **Warning** do not install together with item J.


Back platform (closest to the tailgate)



6


Ensure side-rails are placed underneath the platform.

Back platform (closest to the tailgate)




7

Front platform (closest to cabin).




8 Ensure side-rails are placed underneath the platform.

Front platform (closest to cabin).




9




10

Centre the both platforms on the frame and ensure all gaps are even.

* Add pilot holes to frame before fastening screws.



11



WARNINGS!



**NO STANDING
ON PLATFORM**



**ENSURE
LOAD IS SECURE**

MAX LOAD



**250kg
EVENLY
DISPERSED
LOAD**



**DO "NOT"
OVERTIGHTEN TIE
DOWN STRAPS**



**MECHANICAL
HAZARD**

MAINTENANCE

- Keep the vehicle tub clear of dirt and debris ensuring the smooth operation of the Load Slide.
- Regularly clean the roller track with a clean cloth for smooth operation.

HSP UTE LIDS PTY LTD

40 Overseas Drive, Noble Park North,
Victoria, 3174

(03) 9795 8206

info@hsputelids.com



UNLOCK YOUR VEHICLES POTENTIAL